



MOD-4100

MOD-4100





()	0-3000 / ³	0-1000 m /	H₂S 0-1000 ppm	0-4 %
	±0.1 / ³	±20 m /	±50 ppm	±0.02%
	±1.0 / ³	ASTM D3230	±100 ppm	±0.1%
	5			
	4-12 Barg			
	4100-01-14			
	0-2 Barg			
	4100-01-15			
	10-60 °C			4100-01-
	16			
	3 /			
	5 to +40 °C			
			-40 - +70 °C	
	0-95%			
	-40 to +70 °C			
	ATEX Zone 2			
	Class 1 Division 2 Group C&D T4			
	100-130 VAC 50-60Hz			
	200-260 VAC 50-60 Hz			
	2000 VA 220 VAC			
	5-6 Barg			5-10 /
(H ₂ S)	4-10 Barg 2-5 /			
	4-20 mA			
	RS-485 Modbus, TCP/IP, Fieldbus, Profibus ()			
HMI () -		()		



MODCON SYSTEMS LTD.

Leaders in Analysis, Measurement and Automation



Headquarters: P.O.Box 24121 Akko 2202 Israel, Tel: (9724)9553955, Fax (9724)9553956

E-mail: sales@modcon-systems.com www.modcon-systems.com

Azerbaijan: (99412)4189859 **UK:** (44207)5043626 **USA:** (1917) 5916880 **Russia:**(7495)9891840